

Посібник користувача - Energoefektivnosť / Vadovas - Energijos vartojimo efektyvumo / Manwal ghall-Utent - Efficienza fl-Energija / Kézi - Energiahatékonyág / Příručka - Energetická účinnost / Priručka - Energetika efikasnost / Navodilo - Energetska učinkovitost
Ευχειρίδιο - Ενεργειακή Αποδοτικότητα / Manuel - Enerji Verimliliği / Наръчник - Энергията ефективност / Упутство - Energetska efikasnost / Lámhleabhar Úsáideoir - Éifeachtúlacht Fuinnimh

	PF	UA	LT	MT	HU	CZ	SK	RO	PL	HR	SL	GR	TR	BG	SR	GA
S		EUROLUX BY FABER														
M	305,0616.539															
	P2392															
AEChood	88,6	kWh/a														
EEC	C															
FDEhood	17,2															
FDEC	D															
LEhood	13	lux/Wat														
LEC	D															
GFChood	75,1	%														
GFEC	C															
Qmin	250	m3/h														
Qmax	590	m3/h														
Qboost	N/A	m3/h														
SPEmin	47	dbA														
SPEmax	63	dbA														
SPEboost	N/A	dbA														
P0	0,0	Watt														
Ps	N/A	Watt														
	PI															
F	1,4															
EElhood	81,4															
Qbep	345,0	m3/h														
Pbep	290	Pa														
Qmax	590,0	m3/h														
Wbep	162,0	W														
WL	8,0	W														
Emiddle	100	lux														
Lwa	63	dBa														