Directive EU 65/2014 – EN61591, EN60704-2-13, EN50564	
Brand EUROLUX	
Model REII	ROZO 90PB WH MATT
Annual Energy Consumption (AEC)(kWh/a)	130,3
Energy Efficiency Class (EEI)	D
Fluid Dynamic Efficiency(FDE)	15,0
Fluid Dynamic Efficiency class (FDE) (Indice)	D
Light Efficiency (LE)	6
Lighting Efficiency Class (LE)(indice)	F
Grease Filtering Efficiency (GFE)	58,7
Grease Filtering Efficiency Class (GFE)(indice)	E
Minimum Air Flow in Normal Use MIN (m³/h)	276
Maximum Air Flow in Normal Use(intensive / boost excluded) MAX (m³/h)	507
Air Flow at Intensive/Boost Setting (m³/h)	676
Sound Power Level at Minimum Speed Avaible in Normal Use MIN (LWA)(dB)	53
Sound Power Level at Maximum Speed Avaible in Normal Use MAX (LWA)(dB)	66
Sound Power Level at Intensive/Boost Setting (LWA)(dB)	71
Power Consuption Off Mode (Po)(W)	0,26
Power Consuption in Standby Mode (Ps)(W)	-
Product Information compliant to commission regulation (EU) N	No 66/2014
Time increase factor (f)	1,5
Energy Efficiency (EElhood)	93,9
Measured air flow rate at best efficiency point (QBEP)(m³/h)	351,7
Measured air pressure at best efficiency point (PBEP)(Pa)	283
Measured electric power input at best efficiency point (WBEP)(W)	185
Nominal power of the lighting system (WL)(W)	40,0
Average illumination of the lighting system on the cooking surface (Emiddle)(lux)	260